



# CBL1122

NOV-2-2004

AES/EBU 3 XLR In, 2 XLR Out, BNC in/out to mini26 pin Cable

**History**  
 NOV-02-04 A created  
 NOV-02-04 B clarify what pin on BNC is shell, add connector table

This cable is used for AES/EBU I/O on the ASI6200 series. Cable length is 6 foot.

Connector	Type	Example manufacturer/part number
P1	HD DB26	Norcomp 1080-026-202-001
P2,P3,P4	XLR male	
P7,P8	XLR female	
P11,P12	BNC female	

## 1. Wiring Table

	P1	P2	P3	P4	P7	P8	P11	P12
Type	HD-DB26	Fem XLR	Fem XLR	Fem XLR	Male XLR	Male XLR	Female BNC	Female BNC
Label	-	AES/EBU Sync In	AES/EBU In1	AES/EBU In 2	AES/EBU Out 1	AES/EBU Out 2	Word In	Word Out
Pins...	11	3						
	1		3					
	2			3				
	5				3			
	6					3		
	12						2 (pin)	
	13	1	1	1	1	1	1 (shell)	1 (shell)
	24	2						
	14		2					
	15			2				
	18				2			
	19					2		
	25							2 (pin)
	26	1	1	1	1	1	1	1

[end]